

Serial No. 10/083,656 filed February 25, 2002  
Amendment dated April 12, 2007

RECEIVED  
CENTRAL FAX CENTER

APR 12 2007

### Amendments to the Claims

#### Listing of Claims

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently Amended) An apparatus, comprising:  
a no-spill drinking apparatus, said apparatus comprising an air vent and a valve, said valve comprising a post and a flexible material, said flexible material comprising an opening, said post extending into said opening, said valve having a closed position and in an open position,  
said closed position being a configuration in which liquid is blocked from passage through said opening,  
said open position being a configuration in which liquid can pass through said opening,  
wherein air passes into said apparatus through said air vent and said valve moves from said closed position to said open position upon application of negative pressure to said flexible material, and wherein said flexible material begins to invert upon said application of negative pressure to said flexible material.
2. (Previously Presented) An apparatus as claimed in Claim 1, wherein said post is at least partially tapered.
3. (Previously Presented) An apparatus as claimed in Claim 1, wherein said apparatus comprises a cap for a cup, said cap comprising a soft spout.
4. (Previously Presented) An apparatus as claimed in Claim 1, wherein said apparatus comprises a hard cup.
5. (Previously Presented) An apparatus as claimed in Claim 1, wherein said apparatus comprises an anti-inversion member.

Claims 6-27 (canceled)

Serial No. 10/083,656 filed February 25, 2002  
Amendment dated April 12, 2007

28. (Currently Amended) A apparatus, comprising:

(a) a no-spill drinking apparatus, said apparatus comprising a cap and a cup, ~~said cap being attachable to said cup and detachable from said cup~~, said cap comprising a spout;

(b) a valve, said valve comprising a flexible material having comprising an opening, said valve further comprising a post, said post extending into said opening, said valve having a closed position and an open position, wherein liquid is blocked from passing through said opening and through said spout when said valve is in said closed position;

~~(c) a valve holder which holds said flexible material, said valve holder being attachable to said cap and separable from said cap;~~

(d) ~~(c)~~ an air vent; and,

(e) ~~(d)~~ a valve subunit of said apparatus;

(f) ~~(e)~~ wherein said apparatus is configured such that application of negative pressure through said spout causes said flexible material to move, with said opening of said flexible material moving along said post toward said spout, such that liquid passes through said opening and out of said spout, and air passes into said apparatus through said air vent; and,

(g) ~~(f)~~ wherein upon said application of said negative pressure, said flexible material hits said valve subunit.

29. (Previously Presented) An apparatus according to claim 28, wherein said flexible material begins to invert upon said application of negative pressure.

30. (Previously Presented) An apparatus according to claim 28, wherein said flexible material inverts upon said application of negative pressure.

31. (Previously Presented) An apparatus according to claim 28, wherein said opening is a hole.

32. (Currently Amended) An apparatus according to claim 28, wherein said apparatus comprises an air valve, wherein said air valve air vent comprises an opening, and wherein said opening of said air valve air vent is smaller than said opening of said flexible material of said valve comprising said post.

Serial No. 10/083,656 filed February 25, 2002  
Amendment dated April 12, 2007

33. (Currently Amended) An apparatus according to claim 28, wherein said ~~air vent apparatus~~ comprises an air valve, and wherein said air valve is closed before drinking, and opens during drinking.
34. (Currently Amended) An apparatus according to claim 28, wherein said apparatus comprises an air vent valve, and wherein said air valve opens for passage of air through said air vent valve upon said application of negative pressure.
35. (Currently Amended) An apparatus according to claim ~~28~~ 34, wherein said air vent valve comprises an opening, said opening of said air vent valve being an opening in a flexible material.
36. (Currently Amended) An apparatus according to claim ~~28~~ 34, wherein said air vent valve comprises an opening, said opening of said air vent valve being an opening in a flexible material, said opening of said air vent valve being in a separate flexible material from said flexible material through which passes liquid.
37. (Currently Amended) An apparatus according to claim 28, wherein said apparatus comprises a valve holder, and wherein liquid passes through said valve holder when the a person drinks from said spout.
38. (Currently Amended) An apparatus according to claim ~~28~~ 37, wherein said valve holder and said cap are dimensioned such that said valve holder fits snugly into said cap.
39. (Previously Presented) An apparatus according to claim 28, wherein said post has a greater diameter at its bottom than at its top.
40. (Previously Presented) An apparatus according to claim 28, wherein said post extends tightly through said opening in said closed position.
41. (Currently Amended) An apparatus according to claim 28, wherein further comprising cups of different sizes which are configured for interchangeable attachment to said cap.
42. (Currently Amended) An apparatus according to claim 28, comprising a cup, and wherein said cap is provided with screw threads, such that said cap can be screwed onto and off of the said cup.

Serial No. 10/083,656 filed February 25, 2002  
Amendment dated April 12, 2007

43. (Currently Amended) An apparatus according to claim 28, ~~wherein said cup is comprising~~ a hard cup.
44. (Currently Amended) An apparatus according to claim 28, comprising a cup, and wherein said cap is further provided with finger grips on the outside of said cap to facilitate screwing of said cap on and off of said cup.
45. (Currently Amended) An apparatus according to claim ~~28~~ 34, wherein said application of negative pressure causes a flexible material to move to open said air vent valve.
46. (Previously Presented) An apparatus according to claim 28, wherein said flexible material comprises the shape of a bowl.
47. (Previously Presented) An apparatus according to claim 28, wherein said flexible material comprises the shape of a bowl, said bowl having a rim and a bottom, said bottom moving both toward said rim and toward said spout upon said application of negative pressure.
48. (Currently Amended) An apparatus, comprising:
- (a) a no-spill drinking apparatus, said apparatus comprising a cap ~~and a cup, said cap being attachable to said cup and detachable from said cup~~, said cap comprising a spout;
  - (b) a valve, said valve comprising a flexible material having comprising an opening, said valve further comprising a post, said post extending into through said opening, said valve having a closed position and an open position, wherein liquid is blocked from passing through said opening and through said spout when said valve is in said closed position;
  - (c) a valve holder which holds said flexible material, said valve holder being attachable to said cap and separable from said cap;
  - (d) an air vent valve, said air vent valve comprising an opening; and,
  - (e) a valve subunit of said apparatus, said subunit comprising a shield;
  - (f) wherein said apparatus is configured such that application of negative pressure through said spout causes said flexible material to move, with said opening of said flexible material moving along said post toward said spout, such that liquid passes through said opening and out of said spout,

Serial No. 10/083,656 filed February 25, 2002  
Amendment dated April 12, 2007

and air passes into said apparatus through said vent air valve;

(g) wherein said air vent valve is closed when said valve is in said closed position, and said air vent valve opens upon said application of negative pressure through said spout;

(h) said valve subunit shield being at a sufficiently close distance to said flexible material such that upon said application of negative pressure said flexible material will hit said valve subunit shield.

49. (Previously Presented) An apparatus according to claim 48, wherein said flexible material begins to invert upon said application of negative pressure.
50. (Previously Presented) An apparatus according to claim 48, wherein said flexible material inverts upon said application of negative pressure.
51. (Previously Presented) An apparatus according to claim 48, wherein said opening is a hole.
52. (Currently Amended) An apparatus according to claim 48, wherein said air vent valve comprises an opening, and wherein said opening of said air vent valve is smaller than said opening of said flexible material of said valve comprising said post.
53. (Currently Amended) An apparatus according to claim 48, wherein said air vent valve comprises an opening, and wherein said opening of said air vent valve is an opening in a flexible material.
54. (Currently Amended) An apparatus according to claim 48, wherein said opening of said air vent valve is an opening in a flexible material, said opening of said air vent valve being in a separate flexible material from said flexible material through which passes liquid.
55. (Currently Amended) An apparatus according to claim 48, wherein liquid passes through said valve holder when the a person drinks from said spout.
56. (Previously Presented) An apparatus according to claim 48, wherein said valve holder and said cap are dimensioned such that said valve holder fits snugly into said cap.
57. (Previously Presented) An apparatus according to claim 48, wherein said post has a greater diameter at its bottom than at its top.

Serial No. 10/083,656 filed February 25, 2002  
Amendment dated April 12, 2007

58. (Previously Presented) An apparatus according to claim 48, wherein said post extends tightly through said opening in said closed position.
59. (Currently Amended) An apparatus according to claim 48, wherein further comprising cups of different sizes which are configured for interchangeable attachment to said cap.
60. (Currently Amended) An apparatus according to claim 48, comprising a cup, and wherein said cap is provided with screw threads, such that said cap can be screwed onto and off of the said cup.
61. (Currently Amended) An apparatus according to claim 48, ~~wherein said cup is~~ comprising a hard cup.
62. (Currently Amended) An apparatus according to claim 48, comprising a cup, and wherein said cap is further provided with finger grips on the outside of said cap to facilitate screwing of said cap on and off of said cup.
63. (Currently Amended) An apparatus according to claim 48, wherein said application of negative pressure causes a flexible material to move to open said air ~~vent~~ valve.
64. (Previously Presented) An apparatus according to claim 48, wherein said flexible material comprises the shape of a bowl.
65. (Previously Presented) An apparatus according to claim 48, wherein said flexible material comprises the shape of a bowl, said bowl having a rim and a bottom, said bottom moving both toward said rim and toward said spout upon said application of negative pressure.
66. (Previously Presented) A no-spill drinking apparatus as claimed in claim 1, wherein said opening is against a center stop in said closed position.
67. (Previously Presented) A no-spill drinking apparatus as claimed in claim 28, wherein said opening is against a center stop in said closed position.
68. (Previously Presented) A no-spill drinking apparatus as claimed in claim 48, wherein said opening is against a center stop in said closed position.

Serial No. 10/083,656 filed February 25, 2002  
Amendment dated April 12, 2007

69. (New) A no-spill drinking apparatus as claimed in claim 1, comprising a shield that said flexible material hits upon said application of negative pressure.
70. (New) A no-spill drinking apparatus as claimed in claim 28, wherein said subunit is a shield.
71. (New) A no-spill drinking apparatus as claimed in claim 28, wherein said subunit is a shield, and wherein said flexible material inverts upon said application of negative pressure.
72. (New) An apparatus according to claim 1, wherein said opening is a hole.
73. (New) An apparatus according to claim 1, wherein said apparatus comprises an air valve, wherein said air valve comprises an opening, and wherein said opening of said air valve is smaller than said opening of said flexible material of said valve comprising said post.
74. (New) An apparatus according to claim 1, wherein said apparatus comprises an air valve, and wherein said air valve is closed before drinking, and opens during drinking.
75. (New) An apparatus according to claim 1, wherein said apparatus comprises an air valve, and wherein said air valve opens for passage of air through said air valve upon said application of negative pressure.
76. (New) An apparatus according to claim 75, wherein said application of negative pressure causes a flexible material to move to open said air valve.
77. (New) An apparatus according to claim 75, wherein said air valve comprises an opening, said opening of said air valve being an opening in a flexible material, said opening of said air valve being in a separate flexible material from said flexible material through which passes liquid.
78. (New) An apparatus according to claim 1, wherein said apparatus comprises a valve holder and wherein liquid passes through said valve holder when a person drinks from said spout.
79. (New) An apparatus according to claim 80, wherein said valve holder and said cap are dimensioned such that said valve holder fits snugly into said cap.
80. (New) An apparatus according to claim 1, wherein said post has a greater diameter at its bottom than at its top.

Serial No. 10/083,656 filed February 25, 2002  
Amendment dated April 12, 2007

81. (New) An apparatus according to claim 1, wherein said post extends tightly through said opening in said closed position.
82. (New) An apparatus according to claim 3, further comprising cups of different sizes which are configured for interchangeable attachment to said cap.
83. (New) An apparatus according to claim 1, comprising a cup, and wherein said cap is provided with screw threads, such that said cap can be screwed onto and off of the said cup.
84. (New) An apparatus according to claim 1, comprising a cup, and wherein said cap is further provided with finger grips on the outside of said cap to facilitate screwing of said cap on and off of said cup.
85. (New) An apparatus according to claim 1, wherein said flexible material comprises the shape of a bowl.
86. (New) An apparatus according to claim 1, wherein said flexible material comprises the shape of a bowl, said bowl having a rim and a bottom, said bottom moving both toward said rim and toward said spout upon said application of negative pressure.